



Size A	Part No.*	Across Flats B Max. Min.	Thickness C Max. Min.	Wrench Height D Min.	Flange Dia. E Max.	Proof Load Min. N	1 st Install Max. Nm	1 st Removal Min. Nm	5 th Removal Min. Nm	Weight /1000 Lb.	Carton Qty.
M5x0.8	.5C69268#	8 7.78	7.1 6.74	2.2	11.8	14,800	1.6	0.29	0.2	3.9	10,000
M6x1	.6C69268#	10 9.78	9.1 8.74	3.1	14.2	20,900	3	0.45	0.3	9.5	4,000
M8x1.25	.8C69268#	13	11.1	4.5	17.9	38,100	6	0.85	0.6	18.1	2,000
M8x1	.8F69268#	12.73	10.67			43,100					
M10x1.5	.10C69268#	15 14.73	13.5 13.07	5.5	21.8	60,300	10.5	1.5	1	29.7	1,100
M10x1.25	.10F69268#					67,300					
M10x1	.10X69268#					71,000					
M12x1.75	.12C69268#	18 17.73	16.1 15.67	6.7	26	88,500	15.5	2.3	1.6	50.7	650
M12x1.5	.12F69268#					97,800					
M12x1.25	.12X69268#					102,200					
M14x2	.14C69268#	21	18.2	7.8	29.9	120,800	24	3.3	2.3	66	450
M14x1.5	.14F69268#	20.67	17.68			138,700					
M16x2	.16C69268#	24	20.3	9	34.5	164,900	32	4.5	3	99	300
M16x1.5	.16F69268#	23.67	19.46			185,400					
M20x2.5	.20C69268#	30	24.8	11.1	42.8	259,700	54	7.5	5.3	248	150
M20x1.5	.20F69268#	29.16	23.96								

*Coating Codes (substitute for “#” in the part number).
Other available finishes may not be listed.

DIN 6926 is superseded by ISO 7043

- [blank] – Unfinished Plain
 1 – Zinc/Yellow per ASTM F1941 - Fe/Zn 5C
 2 – Zinc/Clear per ASTM F1941 - Fe/Zn 5AT (RoHS)
 3 – Cadmium/Clear per ASTM F1941 - Fe/Cd 5A
 4 – Phosphate/Oil per ASTM F 1137 Grade D
 C – Commercial Cadmium/Clear
 Y – Commercial Zinc/Yellow
 Z – Commercial Zinc/Clear (RoHS)

Notes:

- These items are compliant to dimensional requirements per DIN 6926
- Threads as specified per DIN 13 part 12
- Prevailing torque per DIN 267 part 15
- Material hardness and Proof load per ISO 898-2 Style 2 (195 min Vickers)
- Non-metallic Insert
 - Material: DuPont Zytel® 101 or equivalent
 - Color: Orange (PMS-165C)
- Six crimps as shown to retain the nylon ring
- Parts listed are not all stocked – contact Aztech sales for lead times
- Latest standard revisions were used on the date of the print release

NYLON INSERT FLANGE LOCKNUTS DIN 6926 CLASS 8



Date	By	Scale	Units	Type	Rev.
10-16-2014	SEK	None	mm	S	A