



Size <b>A</b>	Part No.*	Across Flats <b>B</b> Max. Min.	Flange Dia. <b>C</b> Max.	Thickness <b>D</b> Max. Min.	Wrench Height <b>E</b> Min.	Proof Load Min. Lb.	1 <sup>st</sup> Install Max. In.-lb.	1 <sup>st</sup> Removal Min. In.-lb.	3 <sup>rd</sup> Removal Min. in.-lb.	Weight /1000 Lb.	Carton Qty.
#8-32	8CRFCF#	0.344	0.469	0.203	0.13	1,700	12	2	0.5	3.29	12000
#8-36	8FRFCF#	0.334		0.187		1,750					
#10-24	10CRFCF#	0.375	0.500	0.216	0.13	2100	17	2.5	1.0	5.6	7000
#10-32	10FRFCF#	0.365		0.206		2400					
1/4-20	25CFFCF#	0.438	0.594	0.234	0.14	3,800	40	5.0	1.5	8.84	4500
1/4-28	25FFFCF#	0.428		0.223		4,350					
3/8-16	37CRFCF#	0.562	0.750	0.347	0.23	9,300	110	12	4.0	17.8	2000
3/8-24	37FRFCF#	0.551		0.330		10,500					
1/2-13	50CRFCF#	0.750	1.031	0.458	0.31	17,000	204	22	7.5	44.9	750
1/2-20	50FRFCF#	0.736		0.437		19,200					
5/8-11	62CRFCF#	0.938	1.281	0.569	0.40	27,200	420	39	12.5	87.5	400
5/8-18	62FRFCF#	0.922		0.545		30,700					

\*Coating Codes (substitute for “#” in the part number).  
Other available finishes may not be listed.

[blank] – Unfinished Plain

- 1 – Zinc/Yellow per ASTM F1941 -10 Fe/Zn 5C
- 2 – Zinc/Clear per ASTM F1941 -10 Fe/Zn 5AT
- 3 – Cadmium/Clear per ASTM F1941 -10 Fe/Cd 5A
- 4 – Phosphate/Oil per ASTM F 1137 Grade D
- C – Commercial Cadmium/Clear
- Y – Commercial Zinc/Yellow
- Z – Commercial Zinc/Clear

Notes:

1. Dimensions are compliant to ASME B18.2.2 Table 12 Regular Hex Flange Nuts
2. Performance and material characteristics are compliant to ASME B18.16.6 for Grade B or F.

**REGULAR FLANGE CENTER LOCKNUTS  
GRADE 5**



Date	By	Scale	Units	Type	Rev.
5-14-15	SEK	None	Inch	Sales	A