



Size A	Part No.*	Across Flats B Max. Min.	Thickness C Max. Min.	Across Corners Min.	Bearing Dia. Min.	Proof Load Min. Lb.	1 st Install Max. In.-lb.	1 st Removal Min. In.-lb.	3 rd Removal Min. in.-lb.	Weight /1000 Lb.	Carton Qty.
#8-32	8CFHCA#	0.344 0.332	0.134 0.123	0.378	0.328	1250	12	2	0.5	3.98	10,000
#10-24	10CFHCA#	0.375 0.362	0.172 0.160	0.413	0.357	1550	17	2.5	1	4.8	8,000
#10-32	10FFHCA#					1800					
#12-24	12CFHCA#	0.438 0.428	0.226 0.212	0.488	0.407	2200	27	3.5	1	7.07	5500
#12-28	12FFHCA#					2300					
1/4-20	25CFHCA#	0.438 0.428	0.226 0.212	0.488	0.407	2900	40	5.0	1.5	7.05	5500
1/4-28	25FFHCA#					3300					
5/16-18	31CFHCA#	0.502 0.489	0.273 0.258	0.557	0.465	4700	80	8.0	2.5	10.3	3800
5/16-24	31FFHCA#					5200					
3/8-16	37CFHCA#	0.563 0.555	0.337 0.320	0.628	0.523	7000	110	12	4.0	15.4	2500
3/8-24	37FFHCA#					7900					
7/16-14	43CFHCA#	0.688 0.675	0.385 0.366	0.768	0.641	9550	135	17	5.0	27.7	1400
7/17-20	43FFHCA#					10,700					
1/2-13	50CFHCA#	0.750 0.736	0.448 0.427	0.840	0.699	12,800	204	22	7.5	35.3	1100
1/2-20	50FFHCA#					14,400					
9/16-12	56CFHCA#	0.875 0.861	0.496 0.473	0.982	0.818	16,400	300	30	10.0	57.1	650
9/16-18	56FFHCA#					18,300					
5/8-11	62CFHCA#	0.938 0.922	0.559 0.535	1.051	0.876	20,300	420	39	12.5	71.4	550
5/8-18	62FFHCA#					22,900					
3/4-10	75CFHCA#	1.125 1.088	0.665 0.617	1.240	1.034	30,000	540	58	20	111	350
3/4-16	75FFHCA#					33,600					
7/8-9	87CFHCA#	1.312 1.269	0.776 0.724	1.447	1.206	41,600	840	88	30	176	200
7/8-14	87FFHCA#					45,800					
1-8	100CFHCA#	1.500 1.450	0.887 0.831	1.653	1.377	54,500	1080	120	40	277	125
1-14	100FFHCA#					61,100					

*Coating Codes (substitute for “#” in the part number).
Other available finishes may not be listed.

- [blank] – Unfinished Plain
- 1 – Zinc/Yellow per ASTM F1941 -10 Fe/Zn 5C
- 2 – Zinc/Clear per ASTM F1941 -10 Fe/Zn 5AT
- 3 – Cadmium/Clear per ASTM F1941 -10 Fe/Cd 5A
- 4 – Phosphate/Oil per ASTM F 1137 Grade D
- C – Commercial Cadmium/Clear
- Y – Commercial Zinc/Yellow
- Z – Commercial Zinc/Clear

- Notes:
- Unless Otherwise Indicated, Dimensions per ASME B18.2.2-2010 Table 4
 - Unless Otherwise Indicated, Performance Per IFI 100/107 2002 for Grade A All Metal Prevailing Torque Hex Locknuts.
 - A manufacturer's I.D. mark may appear on the locknut. If there is an I.D. mark, it may be Aztech's or another manufacturer's.

FINISHED HEX CENTER LOCKNUTS GRADE A



Date	By	Scale	Units	Type	Rev.
2-17-14	MJK	None	Inch	Sales	C