



Size <b>A</b>	Part No.*	Across Flats <b>B</b> Max. Min.	Flange Dia. <b>C</b> Max.	Thickness <b>D</b> Max.	Wrench Height <b>E</b> Min.	Flange Height <b>F</b> Min.	Proof Load Min. N	Weight /1000 Lb.	Carton Qty.
M5x0.8	.5CR3S8#	8 7.78	11.8	5 4.7	2.2	1	11,500	3.80	10,000
M6x1	.6CR3S8#	10 9.78	14.2	6 5.7	3.1	1.1	16,300	7.4	5,000
M8x1.25	.8CR3S8#	13 12.73	17.9	8 7.6	4.5	1.2	30,400	15.9	2500
M8x1	.8FR3S8#						40,800		
M10x1.5	.10CR3S8#	15 14.73	21.8	10 9.6	5.5	1.5	48,100	26	1500
M10x1.25	.10FR3S8#						63,600		
M10x1	.10XR3S8#						67,100		

\*Coating Codes (substitute for "#" in the part number). Other available finishes may not be listed.

- [blank] – Unfinished Plain
- 1 – Zinc/Yellow per ASTM F1941 - Fe/Zn 5C
- 2 – Zinc/Clear per ASTM F1941 - Fe/Zn 5AT (RoHS)
- 3 – Cadmium/Clear per ASTM F1941 - Fe/Cd 5A
- 4 – Phosphate/Oil per ASTM F 1137 Grade D
- C – Commercial Cadmium/Clear
- Y – Commercial Zinc/Yellow
- Z – Commercial Zinc/Clear (RoHS)

**Notes:**

1. These items are compliant to all requirements DIN 6923 with Serrations
2. Proof Load and material per DIN 267 part 15
3. Threads as specified in DIN 13 part 12 and 15
4. Parts listed are not all stocked – contact Aztech sales for lead times
5. Latest standard revisions were used on the date of print release

## HEX FLANGE NUTS with Serrations DIN 6923 Class 8



Date	By	Scale	Units	Type	Rev.
10-6-14	SEK	None	mm	S	A