



Size A	Part No.*	Across Flats B Max. Min.	Thickness C Max. Min.	Flange Dia. D Max. Min.	Wrench Height Min.	Proof Load Min. Lb.	Seating Torque In.-Lb.	Weight /1000 Lb.	Carton Qty.
#6-32	6CRSL2#	0.312	0.171	0.422	0.10	820	50	3.57	11,000
#6-40	6FRSL2#	0.302	0.156	0.408		900	55		
#8-32	8CRSL2#	0.344	0.203	0.469	0.13	1250	60	4.82	8000
#8-36	8FRSL2#	0.334	0.187	0.452		1350	65		
#10-24	10CRSL2#	0.375	0.219	0.500	0.13	1650	70	5.98	6500
#10-32	10FRSL2#	0.365	0.203	0.480		1800	75		
1/4-20	25CRSL2#	0.438	0.236	0.594	0.14	2900	108	8.68	4500
1/4-28	25FRSL2#	0.428	0.222	0.574		3300	120		
5/16-18	31CRSL2#	0.500	0.283	0.680	0.17	4700	168	13.2	3000
5/16-24	31FRSL2#	0.489	0.268	0.660		5200	180		
3/8-16	37CRSL2#	0.562	0.347	0.750	0.23	7000	324	18.4	2000
3/8-24	37FRSL2#	0.551	0.330	0.728		7900	348		
7/16-14	43CRSL2#	0.688	0.395	0.937	0.26	9550	480	33.7	1100
7/16-20	43FRSL2#	0.675	0.375	0.910		10,700	516		
1/2-13	50CRSL2#	0.750	0.458	1.031	0.31	12,800	744	46.4	750
1/2-20	50FRSL2#	0.736	0.437	1.000		14,400	816		
5/8-11	62CRSL2#	0.938	0.569	1.281	0.40	20,300	1500	86.0	350
5/8-18	62FRSL2#	0.922	0.545	1.248		22,900	1680		
3/4-10	75CRSL2#	1.125	0.675	1.500	0.46	30,000	2880	146	225
3/4-16	75FRSL2#	1.088	0.627	1.460		33,600	3288		

*Coating Codes (substitute for "#" in the part number).
Other available finishes may not be listed.

- [blank] – Unfinished Plain
 1 – Zinc/Yellow per ASTM F1941 -10 Fe/Zn 5C
 2 – Zinc/Clear per ASTM F1941 -10 Fe/Zn 5AT
 3 – Cadmium/Clear per ASTM F1941 -10 Fe/Cd 5A
 4 – Phosphate/Oil per ASTM F 1137 Grade D
 C – Commercial Cadmium/Clear
 Y – Commercial Zinc/Yellow
 Z – Commercial Zinc/Clear

Notes:

- These items are compliant to all requirements of ASME B18.16.4-2008 for Regular Serrated Flange Locknuts, except that they are not case hardened.

REGULAR SERRATED FLANGE LOCKNUTS



Date	By	Scale	Units	Type	Rev.
2-17-14	MJK	None	Inch	Sales	C