



Size <b>A</b>	Part No.*	Across Flats <b>B</b> Max. Min.	Flange Dia. <b>C</b> Max. Min.	Thickness <b>D</b> Max. Min.	Wrench Height <b>E</b> Min.	Proof Load Min. Lb.	1 <sup>st</sup> Install Max. In.-lb.	1 <sup>st</sup> Removal Min. In.-lb.	3 <sup>rd</sup> Removal Min. in.-lb.	Weight /1000 Lb.	Carton Qty.
1/4-20	25CSFCF#	0.500 0.488	0.906 0.812	0.303 0.290	0.15	3,800	40	5.0	1.5	21.1	1800
5/16-18	31CSFCF#	0.562 0.546	0.968 0.875	0.366 0.353	0.20	6,300	80	8.0	2.5	28.4	1300
3/8-16	37CSFCF#	0.687 0.669	1.093 1.000	0.405 0.392	0.24	9,300	110	12	4.0	44.2	900

\*Coating Codes (substitute for "#" in the part number).  
Other available finishes may not be listed.

- [blank] – Unfinished Plain
- 1 – Zinc/Yellow per ASTM F1941 -10 Fe/Zn 5C
- 2 – Zinc/Clear per ASTM F1941 -10 Fe/Zn 5AT
- 3 – Cadmium/Clear per ASTM F1941 -10 Fe/Cd 5A
- 4 – Phosphate/Oil per ASTM F 1137 Grade D
- C – Commercial Cadmium/Clear
- Y – Commercial Zinc/Yellow
- Z – Commercial Zinc/Clear

Notes:

1. Performance Per IFI 100/107 2002 Grade F

## SUPER FLANGE CENTER LOCKNUTS GRADE F



Date	By	Scale	Units	Type	Rev.
2-17-14	MJK	None	Inch	Sales	B