



Size (E)	Part No.	Across Flats (B)	Thickness (C)	Wrench Height Min. (D)	Bearing Dia. Min.	Proof Load Min. Lb.	1 <sup>st</sup> Install Max. In.-lb.	1 <sup>st</sup> Removal Min. In.-lb.	3 <sup>rd</sup> Removal Min. in.-lb.	Weight /1000 Lb.	Carton Qty.

Drawing Under Construction  
Check with our Sales Department for  
Details on these Parts

\*Coating Codes (substitute for “#” in the part number).  
Other available finishes may not be listed.

- [blank] – Unfinished Plain
- 3 – Cadmium/Yellow per ASTM F1941 -10 Fe/Cd 5C
- 4 – Phosphate/Oil per ASTM F 1137 Grade D
- C – Cadmium/Clear per ASTM F1941 -10 Fe/Cd 5A
- Y – Zinc/Yellow per ASTM F1941 -10 Fe/Zn 5C
- Z – Zinc/Clear per ASTM F1941 -10 Fe/Zn 5AT

Notes:  
1. Threads per ASME B1.1 2003.01.01, 2B Fit Before Lock

## Drawing Under Construction



Date	By	Scale	Units	Type	Rev.
10-21-11	MJK	None	Inch	Sales	A