



Size A	Part No.*	Across Flats B Max. Min.	Thickness C Max. Min.	Wrench Height D Min.	Bearing Dia. Min.	Proof Load Min. Lb.	1 st Install Max. In.-lb.	1 st Removal Min. In.-lb.	3 rd Removal Min. in.-lb.	Weight /1000 Lb.	Carton Qty.
1 1/8-7	112CALNC#	1.689	0.999	0.576	1.603	115,000	1200	150	50	376	90
1 1/8-12	112FALNC#	1.631	0.939			128,000					
1 1/4-7	125CALNC#	1.877	1.094	0.628	1.781	145,000	1320	188	60	538	60
1 1/4-12	125FALNC#	1.812	1.030			161,000					
1 3/8-6	137CALNC#	2.064	1.206	0.693	1.959	173,000	1620	220	70	602	50
1 3/8-12	137FALNC#	1.994	1.138			197,000					
1 1/2-6	150CALNC#	2.250	1.317	0.757	2.138	211,000	1800	260	90	810	35
1 1/2-12	150FALNC#	2.175	1.245			237,000					
1 3/4-5	175CALNC#	2.625	1.540	0.866	2.411	285,000	1800	260	90	1370	20
1 3/4-12	175FALNC#	2.538	1.460			328,500					
2-4.5	200CALNC#	3.000	1.763	1.014	2.755	375,000	1800	260	90	1854	15
2-12	200FALNC#	2.900	1.675			433,500					
2 1/4-4.5	225CALNC#	3.375	1.969	1.271	3.099	26-36 HRC	1800	260	90	2200	10
2 1/4-12	225FALNC#	3.275	1.920								
2 1/2-4	250CALNC#	3.750	2.193	1.261	3.444	26-36 HRC	1800	260	90	4100	6
2 1/2-12	250FALNC#	3.625	2.135								

*Coating Codes (substitute for "#" in the part number).
Other available finishes may not be listed.

- [blank] – Unfinished Plain
- 1 – Zinc/Yellow per ASTM F1941 -10 Fe/Zn 5C
- 2 – Zinc/Clear per ASTM F1941 -10 Fe/Zn 5AT
- 3 – Cadmium/Clear per ASTM F1941 -10 Fe/Cd 5A
- 4 – Phosphate/Oil per ASTM F 1137 Grade D
- C – Commercial Cadmium/Clear
- Y – Commercial Zinc/Yellow
- Z – Commercial Zinc/Clear

Notes:
1. Items of 1 1/2" diameter and smaller are compliant to all requirements of IFI 100/107 for Grade C All Metal Prevailing Torque Hex Locknuts.

AUTOMATION LOCKNUTS GRADE C



Date	By	Scale	Units	Type	Rev
2-17-14	MJK	None	Inch	Sales	D