



Size <b>A</b>	Part No.*	Across Flats <b>B</b> Max. Min.	Thickness <b>C</b> Max. Min.	Flange Dia. <b>D</b> Max. Min.	Wrench Height Min.	Proof Load Min. Lb.	Seating Torque In.-Lb.	Weight /1000 Lb.	Carton Qty.
#6-32	6CRSLH#	0.312	0.171	0.422	0.10	820	50	3.57	11,000
#6-40	6FRSLH#	0.302	0.156	0.408		900	55		
#8-32	8CRSLH#	0.344	0.203	0.469	0.13	1250	60	4.82	8000
#8-36	8FRSLH#	0.334	0.187	0.452		1350	65		
#10-24	10CRSLH#	0.375	0.219	0.500	0.13	1650	70	5.98	6500
#10-32	10FRSLH#	0.365	0.203	0.480		1800	75		
1/4-20	25CRSLH#	0.438	0.236	0.594	0.14	2900	108	8.68	4500
1/4-28	25FRSLH#	0.428	0.222	0.574		3300	120		
5/16-18	31CRSLH#	0.500	0.283	0.680	0.17	4700	168	13.2	3000
5/16-24	31FRSLH#	0.489	0.268	0.660		5200	180		
3/8-16	37CRSLH#	0.562	0.347	0.750	0.23	7000	324	18.4	2000
3/8-24	37FRSLH#	0.551	0.330	0.728		7900	348		
7/16-14	43CRSLH#	0.688	0.395	0.937	0.26	9550	480	33.7	1100
7/16-20	43FRSLH#	0.675	0.375	0.910		10,700	516		
1/2-13	50CRSLH#	0.750	0.458	1.031	0.31	12,800	744	46.4	750
1/2-20	50FRSLH#	0.736	0.437	1.000		14,400	816		
5/8-11	62CRSLH#	0.938	0.569	1.281	0.40	20,300	1500	86.0	350
5/8-18	62FRSLH#	0.922	0.545	1.248		22,900	1680		
3/4-10	75CRSLH#	1.125	0.675	1.500	0.46	30,000	2880	146	225
3/4-16	75FRSLH#	1.088	0.627	1.460		33,600	3288		

\*Coating Codes (substitute for “#” in the part number).  
Other available finishes may not be listed.

- [blank] – Unfinished Plain
- 1 – Zinc/Yellow per ASTM F1941 -10 Fe/Zn 5C
- 2 – Zinc/Clear per ASTM F1941 -10 Fe/Zn 5AT
- 3 – Cadmium/Clear per ASTM F1941 -10 Fe/Cd 5A
- 4 – Phosphate/Oil per ASTM F 1137 Grade D
- C – Commercial Cadmium/Clear
- Y – Commercial Zinc/Yellow
- Z – Commercial Zinc/Clear

Notes:

1. These items are compliant to all requirements of ASME B18.16.4-2008 for Regular Serrated Flange Locknuts.

## REGULAR SERRATED FLANGE LOCKNUTS



Date	By	Scale	Units	Type	Rev.
2-17-14	MJK	None	Inch	Sales	B