



Size A	Part No.*	Across Flats B Max. Min.	Thickness C Max. Min.	Wrench Height D Min.	Proof Load Min. N	1st Install Max. Nm	1st Removal Min. Nm	5th Removal Min. Nm	Weight /1000 Lb.	Carton Qty.
M5x0.8	.5CFJC5	8 7.78	2.7 2.45	2	7,100	2.1	0.35	0.24	1.83	20,000
M6x1	.6CFJC5	10 9.78	3.2 2.9	2.3	10,000	4	0.55	0.4	3.5	11,000
M8x1.25	.8CFJC5#	13 12.73	4 3.7	3	18,300	8	1.15	0.8	7	5,600
M10x1.5	.10CFJC5#	16 17.73	5 4.7	3.8	29,000	14	2	1.4	15.9	2,500
M12x1.75	.12CFJC5#	18 17.73	6 5.7	4.6	42,200	21	3.1	2.1	22.9	1,700
M16x2	.16CFJC5#	24 23.67	8 7.42	5.9	78,500	42	6	4.2	45.2	900
M20x2.5	.20CFJC5#	30 29.16	10 9.1	7.3	122,500	72	10.5	7	88.6	450
M24x3	.24CFJC5#	36 35	12 10.9	8.7	176,500	106	15	10.5	153.2	250

*Coating Codes (substitute for "#" in the part number).
Other available finishes may not be listed.

[blank] – Unfinished Plain

- 1 – Zinc/Yellow per ASTM F1941 - Fe/Zn 5C
- 2 – Zinc/Clear per ASTM F1941 - Fe/Zn 5AT (RoHS)
- 3 – Cadmium/Clear per ASTM F1941 - Fe/Cd 5A
- 4 – Phosphate/Oil per ASTM F 1137 Grade D
- C – Commercial Cadmium/Clear
- Y – Commercial Zinc/Yellow
- Z – Commercial Zinc/Clear (RoHS)

Notes:

1. These items are compliant to all requirements per ISO 4035 with lock
2. Mechanical and performance properties per ISO 2320
3. Material properties of fasteners and Proof Load per ISO 898-2
4. Triangular ISO metric thread according per ISO 965-2 6H
5. Parts listed are not all stocked – contact Aztech sales for lead times
6. Latest standard revisions were used on the date of print release

JAM CENTER LOCK ISO 4035 CLASS 5 with Lock



Date	By	Scale	Units	Type	Rev.
1-12-15	SEK	None	mm	S	B