



Size A	Part No.*	Across Flats B Max. Min.	Thickness C Max. Min.	Wrench Height D Min.	Proof Load Min. N	1 st Install Max. Nm	1 st Removal Min. Nm	5 th Removal Min. Nm	Weight /1000 Lb.	Carton Qty.
M8x1	.8FFJC5#	13 12.73	4 3.7	3	19,600	8	1.15	0.8	7	5,600
M10x1	.10FFJC5#	16 17.73	5 4.7	3.8	32,200	14	2	1.4	15.9	2,500
M12x1.5	.12FFJC5#	18 17.73	6 5.7	4.6	44,000	21	3.1	2.1	22.9	1,700
M16x1.5	.16FFJC5#	24 23.67	8 7.42	5.9	83,500	42	6	4.2	45.2	900
M20x1.5	.20FFJC5#	30 29.16	10 9.1	7.3	136,000	72	10.5	7	88.6	450

*Coating Codes (substitute for "#" in the part number).
Other available finishes may not be listed.

- [blank] – Unfinished Plain
- 1 – Zinc/Yellow per ASTM F1941 - Fe/Zn 5C
- 2 – Zinc/Clear per ASTM F1941 - Fe/Zn 5AT (RoHS)
- 3 – Cadmium/Clear per ASTM F1941 - Fe/Cd 5A
- 4 – Phosphate/Oil per ASTM F 1137 Grade D
- C – Commercial Cadmium/Clear
- Y – Commercial Zinc/Yellow
- Z – Commercial Zinc/Clear (RoHS)

Notes:

1. These items are compliant to all requirements per ISO 8675 with lock
2. Mechanical and performance properties per ISO 2320
3. Material properties of fasteners and Proof Load per ISO 898-2
4. Triangular ISO metric thread according per ISO 965-2 6H
5. Parts listed are not all stocked – contact Aztech sales for lead times
6. Latest standard revisions were used on the date of print release

JAM CENTER LOCK ISO 8675 CLASS 5 with Lock



Date	By	Scale	Units	Type	Rev.
10-17-2014	SEK	None	mm	S	A